


Pneumatic Tacker

Model JK35-590



The JK35-590 is the perfect tool for securing corrugated fibreboard to wood, for example on pallets, frames and other transport packaging. The JK35-590 is a sturdy and stable tool with few moving parts. The ergonomically-shaped handle and low weight ensure that it is easy to use.

The new staple type JK590 provides maximum compression of the corrugated board without breaking through its surface, thanks to the flat and broad design. The tacker uses JK590 staples in leg lengths from 19 to 32 mm. The combination of a wear-resistant tool and a wide-crown staple provides many possibilities for building up strong and robust transport packaging.

For easier service and maintenance of this tool, sets of spares are available, containing parts that are most subject to wear.

Technical data

Length	335 mm (13.2")
Width	65 mm (2.6")
Height	195 mm (7.7")
Weight	2.4 kg (5lb 5oz)
Air pressure	5.5-6 bar (80 to 87 psi)
Max. safe working pressure	7 bar (100 psi)
Air consumption per stroke at 6 bar	0.85 litre
Loading capacity	100 staples

When ordering please use the following article numbers:

126311	Pneumatic Tacker JK35-590
143049	Set of O-rings
143069	Repair kit
400517	Staple JK590-19K (3/4")
400518	Staple JK590-22K (7/8")
400519	Staple JK590-25K (1")
400520	Staple JK590-28K (1 1/8")
400521	Staple JK590-32K (1 1/4")