


Combination Tools

For steel strapping



Pneumatic push-type


Pneumatic push-type combination tools, including the PNSC and PRH-Series models, are used with push-type seals on irregular-shaped packages. Air power tensions, seals and cuts the strapping.



Model	Part Number	Strap Size				Strap Type	Seal Name	Joint Type	Maximum Strap Tension		Weight	
		Width		Thickness					lbs	kg	lbs	kg
		inch	mm	inch	mm							
Pneumatic Push-type												
PNSC 2-12	422495	1/2	12.7	0.017-0.023	0.43-0.58	Apex, Magnus	12 SPC	Single Reverse Notch	700	3 114	9.5	4.3
PNSC 2-58	422496	5/8	15.9	0.017-0.023	0.43-0.58		58 SPC	Single Reverse Notch	700	3 114	9.5	4.3
PNSC 2-34	422497	3/4	19.0	0.017-0.025	0.43-0.64		34 PNSC	Single Reverse Notch	700	3 114	9.5	4.3
PNSC 2-34HT	422881	3/4	19.0	0.017-0.025	0.43-0.64		34 PNSC	Single Reverse Notch	1,000	4 448	9.5	4.3
PRHM-34	306700	3/4	19.0	0.025-0.031	0.64-0.79	Magnus	34 HOC	Double Reverse Notch	1,600	7 117	16	7.3
PRHR-34	424234	3/4	19.0	0.025-0.031	0.64-0.79		34 HOC	Double Reverse Notch	1,600	7 117	34	15.4
PRHR-114	423570	1-1/4	31.8	0.025-0.035	0.64-0.89		114 P	Double Reverse Notch	1,600	7 117	34	15.4

Pneumatic seal-feed

Using applied air pressure as a power source, pneumatic seal-feed combination tools quickly and effortlessly tension, seal and cut the strapping. These tools include the AMP and the AHP.



Pneumatic seal-feed												
Model	Part Number	Width	Thickness	Strap Type	Seal Name	Joint Type	Maximum Strap Tension		Weight			
		inch	mm				lbs	N	lbs	kg		
AMP-1-12	024780	1/2	12.7	0.020-0.023	0.51-0.58	Magnus	12 AMP	Double Notch				
AMP-1-58	024770	5/8	15.9	0.020-0.023	0.51-0.58	Apex, Magnus	58/34 AMP	Double Notch	1,600	7 117	22	10
AMP-1-34	024760	3/4	19.0	0.020-0.025	0.51-0.64		58/34 AMP	Double Notch				
AHP-34	023700			0.031	0.79	Magnus	34 MNT	Double Notch	3,000	13 345	40	18.1
AHP-2-114	015650	1-1/4	31.8	0.025-0.035	0.64-0.89		114 A	Double Notch				



Pneumatic sealless

Pneumatic sealless combination tools include the SLP and the SPC.

Model	Part Number	Strap Size				Strap Type	Joint Type	Maximum Strap Tension		Weight	
		Width		Thickness				lbs	N	lbs	kg
		inch	mm	inch	mm						
Pneumatic sealless											
SLP-12	422350	1/2	12.7	0.017-0.023	0.43-0.58	Apex Plus, Magnus	3 Key	500	2	15	6.4
SLP-58	422355	5/8	15.9	0.017-0.023	0.43-0.58	Apex Plus, Magnus		1,200	5	15	6.4
SLP-34	422360	3/4	19.0	0.017-0.025	0.43-0.64	Apex Plus, Magnus		1,200	5	15	6.4
SPC-3431	422446	3/4	19.0	0.025-0.031	0.64-0.79	Magnus	4 Key	1,600	7	24	10.8
SPC-114	423125	1-1/4	31.8	0.025-0.031	0.64-0.79	Magnus		3,000	13	37	16.8

